

Barrington Packaging Systems Group

Integrated Packaging Equipment, Materials, Production Services and Marketing Support

WRAPPERS

BPS 350 HFFS Flow Wrappers

BPS-350M and BPS-350S Servo

BARRINGTON PACKAGING SYSTEMS

BPS 350



Standard Features

- All Stainless Steel
- Top Chain Conveyor
- No Product-No Film

Options

- Gas Flushing
- Hole Punch Jaws
- Teflon Coated Jaws



The Barrington Warranty covers all parts and labor for a full two-year period.

FEATURES

- Dual frequency conversion control, allows bag to be set and cut in one step, saving film.
- HMI panel for ease in setting parameters.
- Self-diagnosis feature with error message display.
- High sensitivity photocell with digital input of cutting and sealing position for extra accuracy.
- Separate PID temperature control, allowing use of a wide range of packaging materials.
- Positioning stop feature so film will not stick to jaws when machine stops.
- Simple drive system for easy maintenance and reliability.
- Software controlled for easy adjustment and upgrading.

Extra Features in BPS-350S Servo:

- Fewer mechanical parts. Easy to maintain.
- Product size memory feature.
- Extra long bag length.
- Faster packaging speed.
- Electronic adjustment of cutting position
- More accurate package length.
- 3 individual motors (2 servo)

TECHNICAL SPECIFICATIONS

	BPS-350M	BPS-350S
Film Width (Max)	350mm - 13.7"	
Package Size		
Length	80-230mm 3.2-9.1"	80-6000mm 3.2-236"
Width	50-160mm 1.9 - 6.3"	
Height	5-60mm 0.2 - 2.36"	
Max. Film Roll Diam.	300mm - 11.8"	
Machine Speed	25-200ppm	25-230ppm
Machine Size		
Length	3940mm - 155"	
Width	1010mm - 39.8"	
Height	1400mm - 55.1"	
Weight	537kg-1,186 lb	490kg-1,014 lb
Power	220V, 50/60Hz 3.5kw	220V, 50/60Hz 6.15kw

Barrington Packaging Systems Group, Inc.

Toll-Free: (888) 814-7999 • Corporate Headquarters (847) 382-8063
sales@bpsgusa.com • www.barringtonpackagingsystemsgroup.com

