

Barrington Packaging Systems Group

Integrated Packaging Equipment, Materials, Production Services and Marketing Support


WRAPPERS

BPS 450 HFFS Flow Wrappers

BPS-450M and BPS-450S Servo

Standard Features

- All Stainless Steel
- Top Chain Conveyor
- No Product-No Film Registered Wrap



Options

- Gas Flushing
- Hole Punch Jaws
- Teflon Coated Jaws



The Barrington Warranty covers all parts and labor for a full two-year period.

FEATURES

- Dual frequency conversion control, allows bag to be set and cut in one step, saving film.
- HMI panel for ease in setting parameters.
- Self-diagnosis feature with error message display.
- High sensitivity photocell with digital input of cutting and sealing position for extra accuracy.
- Separate PID temperature control, allowing use of a wide range of packaging materials.
- Positioning stop feature so film will not stick to jaws when machine stops.
- Simple drive system for easy maintenance and reliability.
- Software controlled for easy adjustment and upgrading.

Extra Features in BPS-350S Servo:

- Fewer mechanical parts. Easy to maintain.
- Product size memory feature.
- Extra long bag length.
- Faster packaging speed.
- Electronic adjustment of cutting position
- More accurate package length.
- 3 individual motors (2 servo)

TECHNICAL SPECIFICATIONS

	BPS-450M	BPS-450S
Film Width (Max)	430mm - 16.9"	
Package Size		
Length	80-250mm 3.15-9.84"	80-6000mm 13,15-236"
Width	50-180mm 1.96 - 7.08"	
Height	5-65mm 0.2 - 2.56"	
Max. Film Roll Diam.	300mm - 11.8"	
Machine Speed	25-200ppm	25-230ppm
Machine Size		
Length	4130mm - 162"	
Width	930mm - 36.6"	
Height	1540mm - 60.6"	
Weight	644kg-1,420 lb	600kg-1,323 lb
Power	220V, 1 ph 50/60Hz 3.64kw	220V, 1 ph 50/60Hz 6.15kw

Barrington Packaging Systems Group, Inc.

Toll-Free: (888) 814-7999 • Corporate Headquarters (847) 382-8063

sales@bpgusa.com • www.barringtonpackagingsystemsgroup.com

