Barrington Packaging Systems Group

Integrated Packaging Equipment, Materials, Production Services and Marketing Support



BPS 600W HFFS Flow Wrapper

With Reciprocating Jaw





The Barrington Two-Year Warranty covers all parts, all labor, and three preventative maintenance service calls per year.

FEATURES

TECHNICAL SPECIFICATIONS

- Reciprocating jaw for firmer, tighter seal.
- •Dual frequency conversion control, allows bag to be set and cut in one step, saving film.
- HMI panel for ease in setting parameters.
- •Self-diagnosis feature with error message display.
- •Top Chain Conveyer for package compression and better bag appearance.
- High sensitivity photocell with digital input of cutting and sealing position for extra accuracy.
- Separate PID temperature control, allowing use of a wide range of packaging materials.
- Positioning stop feature so film will not stick to jaws when machine stops.
- Simple drive system for easy maintenance and reliability.
- Software controlled for easy adjustment and upgrading.

Film Width (Max) Package Size	600mm	23.6"
Length	120-450mm	4.7 - 17.7
Width	50-200mm	1.9 - 7.9"
Height	10-100mm	0.4 - 3.9"
Max. Film Roll Diam.	320mm	12.6"
Machine Speed	80ppm	
Machine Size		
Length	3980mm	156.7"
Width	930mm	36.6"
Height	1780mm	70.1"
Weight	920kg	2,028 lba
Power	220V, 50/60Hz,3.6kw	
Film Types:	OPP, PVC, OPP/CPP, PT/PE, KOP/CPP, ALU-	
	FILM	