

B Barrington Packaging Systems Group

Integrating
Packaging
Equipment
& Materials



BPS 100 Case & Carton Tape Sealer

**6 TIMES FASTER
THAN BY HAND**

rev 5-8-24

Nothing slows down a fast production and packaging line more than hand taping cases. The sound of a tape gun is like a pocket full of change dropping to the floor - several times per minute. Automatic Case Sealers operate much faster than hand sealing. An operator using an automatic sealer can seal up to 6 times faster than a worker with a hand tape gun.

The BPS 100 Case Sealer is a side belt drive sealer that provides a smooth taping application. Standard features include a roller top in feed and exit table, locking casters and top squeezers to keep your case square as it enters the taping area. All of these standard options and an affordable price make the BPS 100 a fully featured, value priced carton sealer. This remarkable carton sealer comes with a 3" tape cartridge but you can run standard 2 inch x 1500 yd packing tape with out any new adjustments.

TECHNICAL SPECIFICATIONS

Power Supply	110V, 60Hz
Carton Length	6" - inf.
Carton Width	4.7" - 18.9"
Carton Height	4.7" - 18.9"
Tape Length	1000 - 2000 yds.
Tape Width	2" - 3"
Sealing Speed	30 Cartons/min.
Maximum Load	80 lbs.
Machine Size	43" x 35" x 50.3"
Shipping Weight	507 lbs



Barrington Packaging Systems Group, Inc.

Local: (847) 382-8063 Toll-Free: (888) 814-7999 x1 Fax: (847) 382-8064

<https://bpsgUSA.com> sales@bpsgUSA.com

HQ: 835 Barrington Point, Barrington, IL 60010

Showroom: 526 N. York Road Bensenville, IL 60106



B Barrington Packaging Systems Group

Integrating
Packaging
Equipment
& Materials



The Barrington BPS 5050 F is an automatic case sealing machine using pressure-sensitive tape such as PVC or BOPP.

This machine has a wide range of applications including the following industries: chemical fiber, pharmaceutical, publication, refrigeration and air-conditioning, household appliances, ceramics, produce, meats, poultry.

BPS 5050 F Case Taper

TECHNICAL SPECIFICATIONS

Power Requirement	110VAC, 50/60Hz (Single Phase)
Sealing Speed	~30 cartons per minute
Max. Carton Weight	80lbs (36kg)
Tape Width	2-3in (48-72mm)
Carton Length	6in to infinite
Carton Width	4.7-18.9in
Carton Height	4.7-18.9in
Machine Length	43in
Machine Width	35in
Machine Height	50.3in
Weight	507lbs
Operational Environment	32-104°F (0-40°C) @ ≤ 98% Humidity
Machine Noise Levels	≤ 75db

rev 8-22-22

Barrington Packaging Systems Group, Inc.

Local: (847) 382-8063 Toll-Free: (888) 814-7999 x1 Fax: (847) 382-8064

<https://bpsgUSA.com> sales@bpsgUSA.com

HQ: 835 Barrington Point, Barrington, IL 60010

Showroom: 526 N. York Road Bensenville, IL 60106



B Barrington Packaging Systems Group

Integrating
Packaging
Equipment
& Materials

BPS 5050 R



The BPS 5050 R Random Case Sealer is a top and side belt drive sealer that automatically adjusts to the size of the carton within the parameters.

Air-driven cylinders automatically adjust to the height and width of each carton.

Standard features include a roller top in feed and exit table, locking casters and top squeezers to keep your case square as it enters the taping area.

All of these standard features, and the affordable price point, make the BPS 5050 R Random Case Sealer an excellent labor-saving value.

RANDOM Case Taper

TECHNICAL SPECIFICATIONS

Power Supply	110V, 60Hz
Carton Length	6" - inf.
Carton Width	4.7" - 18.9"
Carton Height	4.7" - 18.9"
Tape Length	1000 - 2000 yds.
Tape Width	2" - 3"
Sealing Speed	15 Cartons/min.
Maximum Load	80 lbs.
Machine Size	45.5" x 41.6" x 50.75"
Shipping Weight	661 lbs
Air Consumption	1 CFM @ 80psi

rev 8-22-22



Barrington Packaging Systems Group, Inc.

Local: (847) 382-8063 Toll-Free: (888) 814-7999 x1 Fax: (847) 382-8064

<https://bpsgUSA.com> sales@bpsgUSA.com

HQ: 835 Barrington Point, Barrington, IL 60010

Showroom: 526 N. York Road Bensenville, IL 60106

